

Popsicle / Ice Candy / Kulfi Production Plant

High Quality Material, Advanced Engineering, Salient and Quick Operation, Energy Efficient, Easy to use and Maintain.



Application: Ice Candy ,Roll Cut Ice Cream Machine

Temperature: -26 to 30 Celsius

Freezing Time: Ice Cream Base - 20 to 30 minutes; Water based flavor freezing time

- 30 to 35 Minutes

WWW.WIDECOOL.IN
WWW.HIMALAYAREFRIGERATION.COM









Since the time of our inception, we have been in the field of manufacturing, supplying and exporting ICE CANDY MACHINE. With efficient electrical defrosting system and automatic temperature controls, these products have gained a high demand in the international market. High durability, easy installation and maintenance and resistance against corrosion are some of the main features of Ice Candy Machine. It can be made customized by size and capacity to manual ,semi automatic or automatic mode as per requirement.

POPSICLE / KULFI / ICE CANDY PRODUCTION PLANT							
Model No	RCP100	RCP200	RCP400	RCP800	RCP1000	RCP1600	RCP2000
Capacity (Per Hour)	100	200	400	800	1000	1600	2000
No of Mould	1	2	4	8	10	16	20
Body Dimension	32 x 20 x	32 x 32 x	48 x 32 x	90 x 32 x	104 x 32 x	130 x 32 x	158 x 32
(Inch) (L x B x H)	36	36	36	36	36	36	x 36
Agitator(Qty)	1				2		
Compressor	Embracco Emerson Copland Make						
Refrigerant	R404A						
Construction material	SS 304 Grade						
Power Consumption	0.6	0.9	2.2	3.1	4	5.4	8.6
Power Supply	1 Ph	1 Ph	1 Ph	1 Ph / 3	3 Ph	3 Ph	3 Ph
	• -						_

No of candies depend on type and mould design; Candy Pocket differ by mould and candy shape.









Distinguishing Features:

- Body and Tank made of 304 Grade Stainless Steel for Lifetime Corrosion Resistance.
- Argon welded Tank for leak proof lifetime operation.
- Attractive and robust construction.
- Easy Control and Automatic temperature controller for Energy Efficient operation.
- Specially designed Condensing Unit for Silent working.
- •Defrosting Tank: With Candy Plant a defrosting tank is also used to demould the candy from mould uniformly. It is made of 304 Grade stainless steel with insulation material and temperature to e maintained 45 C by 2KW heater.
- •Choco Coating Tank: It is used to coat candy uniformly by chocolate. It is made of 304 grade SS body and 316 Grade Inner shell Insulated. It is equipped with 2 KW Heater.

